

## Portable Thermal Printer

**Prints Text and Graphics**

*Ideal for providing hard copy data anywhere*

### Features:

- For use with models:
  - 380801/380803 Appliance Tester/Power Analyzer
  - 380900 Dual Channel Datalogging TRMS MultiMeter
  - 382085 Graphic Power Quality Analyzer Clamp
  - 382095/382096 3-Phase Power and Harmonics Analyzer
  - 382410 Graphic Power Analyzer with Flex Probe
  - 407764 Datalogging Sound level Meter
  - 407780 Integrating Sound Level Datalogger
  - 451126 CFM/CMM Vane Anemometer Datalogger
- Prints text and graphics
- Two selectable fonts
- Programmable text header and footer
- Battery and AC powered
- Fixed interval continuous printing (5, 30, 60, 300 seconds)
- RS-232 interface
- Complete with software and cable, AC adaptor, eight AA batteries and roll of paper



### Specifications

Dots per Line:	8 (vertical) x 166 (horizontal)
Fonts:	5 x 7 and 10 x 15
Dot Pitch:	0.35mm (vertical), 0.28 (horizontal)
Character Size:	1.4 x 2.4mm (5 x 7), 2.8 x 4.6mm (10 x 15)
Characters per Line:	27 (5 x 7), 16 (10 x 15)
Printing Contrast:	Auto and user selectable
Printing Width:	46mm
Printing Speed:	0.8 lines/second
Paper Width:	2.24" (57mm)
Interface:	serial RS-232
Receiving Buffer:	9K bytes
Character set:	ASCII International
Graphics:	Bit Map
Batteries:	eight AA batteries
AC Power Adaptor:	12VDC
Dimensions:	3.7x5.3x2.16 (95x135x55mm)
Weight:	15.5oz (440g) including batteries

### Ordering Information:

PR20 .....Portable Thermal Printer  
757057 .....Replacement Thermal Paper (5pk)